


## Technical data

(for standard equipment)



Standard compliance:  
ANSI 92.5-2006,  
CSA B354.1-04



Certified in accordance with DIN EN ISO 9001

### Machine

Minimal length, overall	-	ft/in
Minimal length, overall with basket	20' 4"	ft/in
Minimal width, overall	3' 3"	ft/in
Minimal height, travel position	6' 6"	ft/in
Total weight	6,967	lbs
Live load in traveling position	71.00	psf
Live load in work position	37.60	psf

### Boom system

Max. working height with 441 lbs	74' 10"	ft/in
Max. working height with 882 lbs	-	ft/in
Side reach with 176 lbs	36' 8"	ft/in
Side reach with 441 lbs	36' 8"	ft/in
Side reach with 882 lbs	-	ft/in
Basket load limit	441	lbs
Basket rotation	180	°
Basket dimension (LxWxH)	4'8" x 2'3" x 3'7"	ft/in
Movable jib	-	°
Turret rotation	360	°
Turret rotation, one side narrow	192	°
Turret rotation, both sides narrow	2 x 15	°

### Outrigger system

Width, outriggers deployed max./min.	15' 3"	14' 1"	ft/in
One side narrow, out. depl. max./min.	11' 11"	11' 2"	ft/in
Both sides narrow, out. depl. max./min.	8' 8"	8' 2 1/2"	ft/in
Outrigger plate (LxW)	7 1/2 x 6		ft/in
Stabilization, maximum ground slope	16.5	26	° %
Max. ground clearance	25 1/2		in

### Track system

Height and width track adjustment	9	17 3/4	in
Gradeability	16.7	30	° %
Slope angle	15.5	27	° %
Track (LxW)	4' 9" x 7 3/4"		in
Travel speed	0.8		mph
Max. ground clearance	15 3/4		in

### Engine

Manufacturer	Kubota Z-602		
Horse Power	12.5	17	kw hp
Fuel tank capacity	3.4/Diesel		gal
Manufacturer electric motor	7JB 100 L-04X		
115 V	20	1.7	A kw
400 V	-	-	A kw

Version (date): 07/01/2010

We reserve the right to make technical alterations! All data is approximate!


# TEUPEN®

...work safely aloft

## Technical data (for standard equipment)

# LE23GT

## Working envelope



Standard compliance:  
ANSI 92.5-2006,  
CSA B354.1-04



Certified in  
accordance  
with DIN  
EN ISO 9001

